

Chemical Drum



Avery Dennison drum label materials are designed to perform in extreme labelling environments. They handle heat, cold, rain, snow and salt water. Consistent printability and readability are ensured over the transportation of a drum, through all climate or environmental changes.

Drum labels are typically large, and the portfolio suits application by hand. Materials have high dimensional stability and can meet BS 5609 Marine Test standards for seawater resistance and durability.

Grades are available for UV flexo, thermal transfer and laser printing. A new grade is also available suitable for water-based Inkjet printing, which facilitates GHS compliance for smaller quantities and on-location printing.

Key features

- Large and small labels
- Matt coated filmic grades for superior performance
- Special polyethylene and polypropylene grades for laser applications
- Special grade for water-based Inkjet




Application areas

- Chemical drums and containers
- Point-of-use labels printed on-site at manufacturing and shipping locations
- Labels facing extreme conditions

Product information

| Code | Description | MOQ (m ²) | Width (mm) | Location | Comments |
|--------------------|--|--------------------------|--------------------------------|----------|---|
| F41675.1000 | SYNTHETIC PAPER CD303 BG40WH N | 1000 | Ready Width (200, 250, 333) | AUS | - Suitable for Thermal Transfer printing |
| F50150.1000 | DATA PE80 CD303 BG40WN | 1000 | Ready Width (200, 250, 333) | AUS | - Suitable for Thermal Transfer printing - Complies with BS 5609, Section two, Marine Immersion Test |
| 9171.1060 | DATA FLEX CD303 B100 | 1060 | 530 | AUS | - Suitable for Laser printing |
| ADS1389 | Synthesis Paper3 HP104 BG40WH imp | 1530 | 765 | ASEAN | - Suitable for Thermal Transfer printing - Complies with BS 5609, Section two, Marine Immersion Test |
| OZ2180 | 127µ Inkjet Synthetic Paper Premium AF101 BG40Wh Imp | 1530 | 1530 | ASEAN | - Suitable for Inkjet printing - Complies with BS 5609, Section two, Marine Immersion Test |
| AF170 | PE100 WHITE S277 BG45WH IMP | 2000 | 2000 | EUR | - Suitable for Thermal Transfer printing - Complies with BS 5609, Section two, Marine Immersion Test |
| AF172 | PE100 TOP WHITE S277 BG45WH IMP | 2000 | 2000 | EUR | - Suitable for Thermal Transfer printing - Complies with BS 5609, Section two, Marine Immersion Test |
| AN025 | TRANSFER PEHD105 S2045N BG40BR | 1000 | 1000 | EUR | - Suitable for Thermal Transfer printing - Complies with BS 5609, Section two, Marine Immersion Test |
| AM664 | TRANSFER PEHD105 S445N BG40BR | 1000 | 1000 | EUR | - Suitable for Thermal Transfer printing - Complies with BS 5609, Section two, Marine Immersion Test |
| AB655 | CO EX100 S445N BG45WH 1000 1000 EU | 1000 | 1000 | EUR | - Complies with BS 5609, Section two, Marine Immersion Test |

Find more label solutions at label.averydennison.com

Connect with us on:   



DISCLAIMER – All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.averydennison.com>. © 2021 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its contents and product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part of purposes other than marketing by Avery Dennison.